

Image Deconvolution using SVI Huygens

Image deconvolution is a powerful image restoration method which can reverse some of the optical distortions introduced by microscopes.

Written By: Dominik Hänni



INTRODUCTION

This guide is an introduction to image deconvolution using the commercial software package <u>SVI</u> <u>Huygens</u>.

Huygens allows deconvolution of various types of microscopy images but this guide is intended to cover images acquired through **widefield**, **confocal** and **multiphoton** systems.

Optical imaging systems such as microscopes produce an image of a real world object by convolving it with the so called point spread function (PSF). In simple terms the PSF is the 3D image of a point source imaged by using a particular microscope and mostly determined by

- the used objective,
- the wavelength of the light,
- the refractive index of the immersion and sample media

Deconvolution is the mathematical process of inverting this convolution and therefore trying to find back the real world object.

The PSF of a particular microscope configuration can either be measured using sub-resolution beads or calculated using the known microscope, objective and sample parameters.

Due to noise contributions and statistical limitations, deconvolution is a so called ill-posed problem which needs an **iterative approach**. This means that there is not one single, correct deconvolution result but parameters (e.g. number of iterations, signal to noise ratios and quality thresholds) need to be set and might be further optimized.

The first version of this guide was written using SVI Huygens Professional for Win64 (18.10.0p5 64b). It was written with a beginner in mind and by optimizing some steps and/or tweaking some parameters, better results might be achieved.

Step 1 — Nyquist sampling

S Nyquist rate a	and PSF calcula	tor	This is the parameter list used in this calculation	n:
Microscope type	Confocal	\$	Parameter	Value
			Microscope type	Confocal
Numerical aperture	1.3		Numerical aperture	1.4
Excitation wavelength	488	nm	Excitation wavelength	488
			Emission wavelength	520
Emission wavelength	520	nm	Number of excitation photons	1
Number of excitation photons	1		Lens immersion refractive index	1.515
Lens immersion refractive index	Oil \$ 1.515	5	The optical axis lays along z. Your Nyquist sam	ppling is:
	Calculate a Point Sprea	ad Function	x: 43 nm	
			y: 43 nm	

Proper x-y-z sampling on the microscope (called Nyquist sampling) is a fundamental requirement for performing successful image deconvolution.

Out of focus information is very important for deconvolution. Therefore, it is always recommended to deconvolve 3D image datasets.

- On a scanning confocal microscope you can adjust the x-y sampling by either changing the zoom or the image size and therefore changing the pixel size.
- The z sampling can be adjusted by selecting the proper spacing between the slices of a 3D stack.
- If you are unsure about the needed x-y pixel size and z spacing for optimal Nyquist sampling using your objective and microscope settings you can use the <u>SVI Nyquist Calculator</u>.

Step 2 — SVI Huygens



- Reserve and open a ZMB image processing virtual machine.
- Start Huygens Professional.

Step 3 — Open an image file



- On the main menu bar click "Open".
- Supported file formats include .lif (Leica), .czi (Zeiss) as well as .tif files.
- If you open a Leica .lif which can contain multiple datasets, Huygens asks you to make a selection.
- When opening a .tif series, Huygens will ask how to interpret the individual files. Such as slices from a 3D stack or time points.

Step 4 — Checking the imported file



- After opening a file, you should find a new thumbnail in the main work space.
- Richt click on the thumbnail and "2D visualization/Slicer" opens the image in a slicer view and allows you to check if the data was imported properly.

Step 5 — Microscopic parameters

		Task reports S A more recent Huy https://svi.nl/d Failed to open in 2:/zmbstaff/386 Operation cancel Failed to open in 2:/zmbstaff/386 on_Pinhole_0.5AU Error: command in Force.command in	Contraction of the second sec	Channel parameters Select channel 1. Contocal 2. Contocal	Image properties Two_Cells_Printele_0.54U_typulat Dimensions: 4/s0-2640-664-0 Channels: 4/stocked Data type: byte
a b	Microscopic parameters Deconvolution Express Deconvolution Wizard Operations Window Additional restoration • Twin Slicer 2D visualization • 3D visualization • Analyze image • Thumbnail settings • Save as • Delete image	<pre>E Huygens Tcl Scripting</pre>	Z (nm) 130.177 Optical parameters: Remercial aperture 3400 Refractive inforces: 151.9 e Embedding med. Gipc 90% + 4468 Dat Advanced: - n_1 • Objective quality Good ~ Coversite: Launch estlor [2] • Coversite: Coversite: Launch estlor [2] * Coversite: Launch estlor [2] * SAU Upward ~ SAU -	Accellence Accellence Morace op type Confocal Packaprojected pinhole (nm) Eactation wavelength (nm) 405 Andreas charace Multip shock exclusion Eactation fill factor Zeo Xet all parameters verified Set all verifies	Sce 1768 Templates: I could See Reports: Reports: Retractive index memory. The X sampling is to large. The X sampling is to large. The X sampling is to large. Recent Cancel Accest
RAM:	3% VRAM: -	MiB			

A For a good deconvolution, correct microscope, image and sample parameters are very important.

- Right click on your image thumbnail and select "Microscopic parameters".
- Parameters are read from the image metadata.
- Depending on the source file format this parameters might or might not be correct. Check and correct them very carefully.

Step 6 — Microscopic parameters: General parameters

Edit Microscopic Parameters - Two_Cells_Pinhole_0.5AU_nyquist			Select channel: Two_Cells_Pinhole_0.5AU_nyquist			
			0: Confocal	Dimensions: 2640×2640×64×0		
General parameters	Channel parameters		1: Confocal	E Channels: 4 (stacked)		
Sampling intervale:	Select channel	Two_	2: Confocal 3: Confocal	Data type: byte Size: 17 GiB		
Samping intervals.	0: Confocal	Dimensions:	Microscope type			
X (nm) 58.734	1: Confocal	Channels:	Contocal	Templates:		
Y (nm) 58.734	2: Confocal 3: Confocal	Data type: Size:	Backprojected pinhole (nm) 143			
Z (nm) 130.177	Microscope type Confocal -	-	Excitation wavelength (nm) 405	пероно.		
Ontical parameters	Backprojected pinhole (nm)	remplates:	 Emission wavelength (nm) 429 	Refractive index mismatch. The embedding medium refractive index is very close to the		
Opical parameters.	Excitation wavelength (nm)		Multi photon excitation	NA. The X compliantic fee large		
Numerical aperture 1.400		Refractive index m		The Y sampling is too large.		
Refractive indexes:	Emission wavelength (nm) 429	The embedding m NA.	Excitation fill factor 2.00	Please consult the Nyquist Calculator for optimal sampling		
Lens immersion Oil 👻 1.518	Multi photon excitation	The X sampling is The Y sampling is		intervals.		
● Embedding med. Glyc 90% ▼ 1.458	Excitation fill factor 2.00	Please consult the				
Advanced		intervers.				
Advanced.						
Objective quality Good						
Coverslip: Launch editor 🛃						
Coverslip position (µm) 0.000						
Imaging direction Upward -						
				-		
Help	X Not all parameters verified Set all verified	Re	X Not all parameters verified Set all verified	Revert Cancel Accept		
	Set all verified					

- Here you can check and set the general imaging settings.
- By the background color and in the "Reports" field, Huygens gives you feedback about issues with your imaging settings or parameters.
- A The refractive index of your sample/embedding media is only known to you and therefore has to always be set correctly.

Step 7 — Microscopic parameters: Channel parameters



- Specify the microscope type as well as the excitation and emission wavelength for each acquired channel.
- For a bandpass emission filter you can use the center wavelength.
- For multiphoton images you can select "Widefield" and set the "Multi photon excitation" to 2.
- For standard microscopes the "Excitation fill factor" is at least 2 or higher.
- For confocal microscope data the "Backprojected pinhole (nm)" is usually calculated correctly from the metadata. More information <u>here</u>.

Step 8 — Microscopic parameters: Save and accept

	Select channel: Confocal Confocal	•	Two_(Dimensions: Channels: Data tune:	Cells_Pinhole_0.5AU_nyquist 2640×2640×64×0 4 (stacked) hyte					
Astronomy and the second	Contocal scope type projected pinhole (nm) atton wavelength (nm) photon excitation attion fill factor	Confocal 143 405 429 1 2.00	Size: Templates: Refractive index mis The embedding me NA. The Y sampling is t Please consult the f intervals.	1.7 GB	General parameters Sampling intervals: X (zm) 4023 Y (zm) 6023 Z (zm) 1501 Optical parameters: Numerical apentive 1400 Refractive indisces: 1400 Less immersion 014 1518 Advanced 000 0000 Coversitip: Laund 0.000 Imaging direction Ugen	Channel param Select channel Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control Control C	eters : Contocal 43 445 425 1 2 00 Sat all writing	Image properties Two_Cells_Initiole_0.54U_sryouts Doments: 2440-244 Obanets: 2440-2440	0=64+0 Jtacked) byte 17 GB are o be jling
*	Kot all parameters verified Se	at all verified	Rev	ert Cancel Accept					

- If you acquired multiple datasets with the same parameters, you can save them as a template for further use or batch processing.
- After careful revision of all your parameters you can click "Set all verified" followed by "Accept".
- Your data is parametrized and ready for deconvolution.

Step 9 — Deconvolution wizard



- Right click on the image thumbnail and click "Deconvolution Wizard".
- You can see some of the previously defined parameters as well as warnings about your sampling in the "Wizard status" field.
- Click "Enter wizard".



Step 10 — Deconvolution wizard: PSF selection

- In this step you could select a measured point spread function (PSF). Usually we recommend to use a calculated one.
- To automatically calculate the PSF from your parameters just click next.

Step 11 — Deconvolution wizard: Cropping



- Deconvolution is a computationally expensive operation and can take quite a bit of time. In order to reduce the amount of data increasing the speed, you can crop your dataset to an area of interest.
- You can crop the 3D stack by clicking "Launch the Cropper".
- Adjust the area of interest by adjusting the cropping lines.
- Click "Crop" when you are done .
- Press next.



Step 12 — Deconvolution wizard: Select channel

- If you have more than one channel in your dataset, you will need to deconvolve them sequentially.
- You can see all the channels of your dataset in the left column.
- Select the first channel in the "Channel" selection and press next.

Step 13 — Deconvolution wizard: Inspecting the image histogram



- In this step you will calculate and inspect the image intensity histogram of the selected channel.
- Select "Logarithmic" and click "Compute".
- Huygens will compute and show the histogram as well as give information about the intensity distribution, such as the number of clipped/saturated voxels.
- If you have clipped voxels (saturated pixels) you can still proceed with the deconvolution. However, good image statistic without clipping is important for a successful deconvolution. We strongly recommend to carefully consider this during your next image acquisition.
- Press next.

Step 14 — Deconvolution wizard: Background



- Background is any additive and approximately constant signal in your image that is not coming from the objects you are interested in.
 Background includes e.g. an electronic offset in your detector, or indirect light.
- For low noise detectors such as the photon counting hybrid detectors (HyD) on Leica confocal systems, select "Manual" and put it to 0.
- Alternatively Huygens can also automatically estimate the background based on a circular search area. For this press ("Auto").
- Background removal changes the total image intensity during deconvolution. This can be problematic for quantitative fluorescence experiments.

Step 15 — Deconvolution wizard: Background estimation and deconvolution algorithm

	-8.609 -8.609 50 100 150 Intensity	200 250	Suggestions for te	sting algorithms		
Help Reports	Estimating parameters		We suggest to start with the defaul	t algorithm (+++) and then test also	o other algorithms (++ a	and +).
ating parameters	Background Estimation: automatic mode			CMLE	QMLE	GMLE
stage the background of the measured image is	Background to be used during deconvolution	0.0500				
ated over a small volume. sult is copied to the 'Absolute background' field.	Deletive background	0.0609	Widefield	+++	**	+
an modify this value directly or indirectly by entering	Log absolute background instead of relative in template	0.0	Confocal	+++		++
tive background value in the form of a percent	E Log absolute background instead of relative in template.	Spipping dick				
ample, to double the absolute value enter +100, to		Spinning disk				
e it by 10% specify -10 in the field below.	Select deconvolution algorithm	0111.5	STED	+++		++
this is confocal data you have the choice between the fast Good's roughness GMLE method or the t CMLE method.		CMLE	SPIM	***		
Wizard status						
Cells_Pinhole_0.5AU_nyquist.	•					
Two_Cells_Pinhole_0.5AU_nyquist is sampled	Account					
	Accept	S				

- If you used automatic background estimation you can see the results in this step.
- Here you can also choose between different deconvolution algorithms.
- CMLE (Classic Maximum Likelihood Estimation) is the most general restoration method available, valid for almost any kind of images. It uses significantly less memory than GMLE. Usually the method of choice.
- (i) **GMLE** (Good's roughness Maximum Likelihood Estimation algorithm): Gives faster results (less iterations) with very noisy data such as low light confocal and STED. But uses a lot of memory.
- (i) **QMLE** (Quick Maximum Likelihood Estimation) is a deconvolution algorithm that gives good and fast deconvolution results on low-noise widefield images. (Not available when you deconvolve confocal images)
- Check the background estimate, select the deconvolution algorithm and press "Accept".

Step 16 — Deconvolution wizard: Signal to noise ratio

			4 325.3 -8.609 E-01	50	100 Inter	150 nsity	200	250
Help	Reports		Deco	nvolution s	etup			
, based on results from the previous stages. leconvolution is done in an iterative fashion. The ons continue until either a maximum number of ons is reached or some quality measure.		The result will be Below are the de these values. Maximum iteratio	stored in image deco fault values for decom	on:Ch0. volving ima	ges. If n	ecessary	you can cha	ange
nvolution.		Signal to noise ratio					20	
liso: About deconvolution		uany mesnora Iteration mode					0.05 Optimized -	
Wiza	rd status	Brick layout					Auto	
Cells_Pinhole_0.5AU_i e Two_Cells_Pinhole_(rsampled	nyquist. D.5AU_nyquist is		Deconvoluti	ion preview			Deconvolve	
								57

- The "Signal to noise ratio" (SNR) controls the sharpness of the restoration result. The higher this value, the sharper your restored image will be. It is the most important parameter for deconvolution.
- However using a too large SNR value might be risky when restoring noisy originals, because you could be just enhancing noise.
- A noise-free widefield image usually has SNR values higher than 50.
- A noisy confocal image can have values between 15-20.
- In the Huygens Software the SNR of a digital image is defined as the square root of the number of photons in the brightest part of the image.
- If you use a confocal with photon counting detectors (e.g. Leica HyDs in photon counting mode), the SNR is the square root of the highest pixel intensity in your image.
- Also check the <u>SVI Huygens</u>
 <u>webpage</u> for further information about the SNR.
- The remaining options usually don`t need any adjustments.

Step 17 — Deconvolution wizard: Preview and deconvolution



- To check the choosen deconvolution parameters you can click on "Deconvolution preview".
- In the image window you can see now a yellow box which previews the result of the deconvolution.
 If you are not happy or start seeing artifacts, you might need to adjust the deconvolution parameters such as the SNR.
- If the preview looks good, you can click "Deconvolve" which starts the deconvolution of the active channel.
- The progress of your deconvolution can be seen in the "Reports" window. Keep in mind that deconvolving a dataset might take some time.

Step 18 — Deconvolution wizard: Deconvolution result



- When the deconvolution of your channel is done, you can see a preview of the result in the "Deconvolution result" step.
- Click "Accept, to next channel" to deconvolve the next channel of your dataset.
- For the next channel, the wizard starts again on Step #12.
- Perform a deconvolution for all channels of your dataset.
- After deconvolution of the last channel click "All done".

Step 19 — Deconvolution wizard: Select the results



 In this step you can select and merge the resulting channels.
 Usually nothing needs to be done here and you can click "next".

Step 20 — Deconvolution wizard: Summary



- In the last step you can save your deconvolution parameters as a template. This can be useful if you deconvolve multiple datasets of the same type.
- Click "Done" to close the deconvolution wizard.

Step 21 — Back to workspace: Saving your results



- Back on the Huygens workspace you will find a new thumbnail with your deconvolution results.
- Save your results by right clicking on the results thumbnail and "Save as/...".
- Usually saving your results as .tif is a good choice.
- A "Question" dialog asks you how you want to save your files. Usually "One per channel and slice" is recommended.

Step 22 — Saving the results: Conversion mode



- Depending on the choosen file format and the intensities in your data, Huygens might also ask about the conversion mode.
- Contrast stretch: positive data range for each channel is adapted to the Tiff range, the different perchannel factors are not reported.
- (i) Linked scale: as stretch, but now the relation between channels is retained: the same factor is applied to all channels that stretches the one with maximum intensity to the Tiff range. The factor is reported by Huygens.
- (i) Clip: positive data outside the Tiff range is clipped to that range.
- If the data is solely used for visualization purposes, "Contrast stretch" can be a good option. If ratiometric analysis of images is needed, then "Linked scale" might be the better option.
- Please also read <u>this article</u> if you are unsure about what to choose here.

Step 23 — Exploring the results: Twin slicer



- Finally, right click on the thumbnail and click "Twin Slicer".
- In the drop down menu you can select your raw dataset on the left and your deconvolved dataset on the right for direct comparison of the deconvolution result.

If you are done with your deconvolution please save your data and close Huygens. Due to the license model we have with SVI we pay by usage. So idle Huygens session do cost us money. Thanks and good deconvolutions!